



**AMPLIFIER  
RESEARCH**

50W1000BM1-M3


Rad, Souderton, PA 18964-9990 USA  
TEL 610 251 7200 FAX 610 251 7200

MODELS 50W1000B, M1, M2 M3  
50 WATTS CW  
1 - 1000 MHz

*This update adds a 3dB output power graph to the spec sheet.*

The Model 50W1000B is a portable, self-contained, air-cooled, broadband, solid state amplifier designed for applications where instantaneous bandwidth and high gain are required. Push-pull circuitry is utilized in the high power stages to lower distortion and improve stability. The 50W1000B, when used with an RF sweep generator, will provide a minimum of 50 watts of swept power. Included is a front panel gain control which permits the operator to conveniently set the desired output level. The 50W1000B is protected from RF input overdrive by limiting diodes and an RF input leveling circuit which controls the RF input level to the RF amplifier first stage when the RF input level is increased above 0 dBm. The RF Amplifier stages are protected from over temperature by removing the DC voltage to them if an over temperature condition occurs due to cooling blockage or fan failure. There is a digital display on the front panel to indicate the operate status and fault conditions when an over temperature, power supply, or amplifier fault has occurred. The unit can be returned to operate when the condition has been cleared. The 50W1000B includes digital control for both local and remote control of the amplifier. This 8-bit RISC microprocessor controlled board provides both IEEE-488 (GPIB) and asynchronous, full duplex RS-232 control of all amplifier functions.

#### 50W1000B TYPICAL POWER OUTPUT



REV020199

**SPECIFICATIONS**  
**Model 50W1000B**

<b>RATED OUTPUT POWER</b> .....	50 watts minimum
<b>INPUT FOR RATED OUTPUT</b> .....	1.0 milliwatt maximum
<b>POWER OUTPUT @ 3dB COMPRESSION</b>	
Nominal.....	70 watts
Minimum.....	50 watts
<b>POWER OUTPUT @ 1dB COMPRESSION</b>	
Nominal.....	55 watts
Minimum.....	40 watts
<b>FLATNESS</b> .....	±1.0 dB typical ±1.5 dB maximum
<b>FREQUENCY RESPONSE</b> .....	1-1000 MHz instantaneously
<b>GAIN (at maximum setting)</b> .....	47 dB minimum
<b>GAIN ADJUSTMENT (Continuous Range)</b> .....	20 dB minimum (4096 steps remote)
<b>INPUT IMPEDANCE</b> .....	50 ohms, VSWR 2.0:1 maximum
<b>OUTPUT IMPEDANCE</b> .....	50 ohms, nominal
<b>MISMATCH TOLERANCE *</b> .....	100% of rated power without foldback. Will operate without damage or oscillation with any magnitude and phase of source and load impedance.
<b>MODULATION CAPABILITY</b> .....	Will faithfully reproduce AM, FM, or pulse modulation appearing on the input signal
<b>HARMONIC DISTORTION</b> .....	Minus 20 dBc maximum at 50 watts
<b>THIRD ORDER INTERCEPT POINT</b> .....	57 dBm typical
<b>PRIMARY POWER (selected automatically)</b> .....	90-132, 180-264 VAC 50/60 Hz, single phase 600 watts maximum
<b>REMOTE INTERFACES</b> .....	IEEE-488, RS-232
<b>CONNECTORS</b>	
RF.....	Type N female
<b>REMOTE CONTROL</b>	
IEEE-488.....	24 pin male
RS-232.....	9 pin Subminiature D (male)
<b>REMOTE INTERLOCK</b> .....	15 Pin Subminiature D
<b>COOLING</b> .....	Forced air (self contained fans)
<b>WEIGHT</b> .....	See Model Configurations
<b>SIZE (WxHxD)</b> .....	See Model Configurations
* See Application Note #27	

**MODEL CONFIGURATIONS**

MODEL NUMBER	RF INPUT	RF OUTPUT	WEIGHT	WEIGHT
50W1000B	Type N female on front panel	Type N female on front panel	25.9 kg (57.0 lb)	50.3 x 20.3 x 45.7 cm 19.8 x 8.0 x 18.1 in
50W1000BM1	Type N female on rear panel	Type N female on rear panel	25.9 kg (57.0 lb)	50.3 x 20.3 x 45.7 cm 19.8 x 8.0 x 18.1 in
50W1000BM2	Same as 50W1000B with enclosure removed for rack mounting		16.4 kg (36.0 lb)	48.3 x 17.8 x 46.0 cm 19.0 x 7.0 x 18.1 in
50W1000BM3	Same as 50W1000BM1 with enclosure removed for rack mounting		16.4 kg (36.0 lb)	48.3 x 17.8 x 46.0 cm 19.0 x 7.0 x 18.1 in